

Portable Forklift Loading Ramp



Safe Working Load: 8 Tons

Size: 8.4 m slope Length X 3.0m level off X 2.1m width.

Height adjustment: 1.3m-1.8m (Customizable)

Materials list: Steel Structure with Beams and Box Sections

Specifications:

Landing Gear:

FUWA brand, mainly use for the big container truck.

Model: FW 28E Landing gear

Static Load / Pair: 80,000 Kg

Hydraulic Jack:

Special Hydraulics provided which provides ease in height adjustments and additional support.

PROVIDER OF LIFESTYLE & INDUSTRIAL SCALES

P.O. Box: 40646, Plot No: 613-1124, Ras Al Khor Industrial Area II, Aweer, Dubai – U.A.E.
Tel: +971 4 3337789 / 90. Fax: +971 4 3336210. E-mail: info@accuratemeezan.com

Wheels for Mobility:

Rubber solid wheels (Same as forklift wheels) to provide very easy mobility.

High Traction Grating:

To be provided on top of the ramp for skid off protection.

Safety Railings:

To be provided to cut back the danger of accidental run-off and alternate loading mishaps

Strong safety chains:

10 mm chains to lock in the ramp to the trailer

Easy access plates:

Hinge plates shall allow to enter and exit the container.

Visibility:

High quality synthetic oil paint Black and Orange safety rails.

Warranty:

3 Years Structural Warranty

Certificates:

3rd Party Load test Certificate from a DM approved organization.

